

IN THE SPECIFICATION:

Please add the following at the beginning of the specification:

1. **Related Cases**

This is a continuation co-pending Serial No. 10/216,539, entitled "Lighting Structure for Patio Umbrella", filed August 9, 2002, whose disclosure is incorporated by this reference as though fully set forth herein.

Please add the following paragraph on page 2, line 25:

--As used herein, the terms "lighting device 10" and "lighting structure 10" shall mean the same element.--

Please amend the paragraph on page 3, line 32 to page 4, line 8 as follows:

In use, the user positions the inner piece 56 at a selected location along the pole 52, and then aligns the outer piece 58 to the inner piece 56 at the selected location so that the two pieces 56, 58 form a circular unit. The user then attaches the outer piece 58 to the inner piece 56 by threading the bolt 70 through the bores of the recesses 66 and 68, and tightening the nut 92 to tightly secure the entire collar 50 to the selected location along the pole 52. Next, the battery housing 12 can be secured to the inner piece 56 by sliding the sliding groove 90 along the concave outer surface 82 of the battery housing 12 over the extension 88 of the collar 50. The sliding groove 90 has a stop edge 98 that abuts the top of the extension 88 to prevent the battery housing 12 from sliding off the extension 88. At this time, the switch 32 can be turned on or off to turn on or off the light bulb 20.